

MATTINGLY, STANGER & MALUR, P.C.

JOHN R. MATTINGLY*
DANIEL J. STANGER
SHRINATH MALUR*

GENE W. S. PTO
Of Counsel
JEFFREY M. SCHUM
SCOTT W. HARKNER
Registered Patent Agents
* Bar Members in Other Than Virginia

ATTORNEYS AT LAW
104 EAST HUME AVENUE
ALEXANDRIA, VIRGINIA 22301

(703) 684-1120

PATENT, TRADEMARK
AND COPYRIGHT LAW
FACSIMILE: (703) 684-1157

Jc896 U.S. PTO
09/649962
08/29/00

Date: August 29, 2000

Attorney Docket No. NIP-201

To: Assistant Commissioner for Patents
Washington, D.C. 20231

Sir: Transmitted herewith for filing is the patent application of:

Inventor: T. KAWASAKI et al (See Attached List)

For:
RADIOACTIVE WASTE TREATMENT FACILITY

Enclosed are:

☐

5 Sheets of Drawings

☐

This application is being filed without an executed Declaration.

☒

Priority is claimed from Japanese Application No. 11-356466
filed December 15, 1999. ☐ A certified copy is attached herewith.

☒

Copies of the disclosure documents listed on the attached PTO 1449 form and
☒ discussed in the specification or ☐ attached Information Disclosure Statement.

☐

A verified statement to establish small entity status under 37 CFR 1.9 and 1.27.

☒

Specification: Abstract ☒, Description 26 pages; and 4 claim(s).

☐

Preliminary Amendment.

☒

Executed Declaration.

The filing fee is calculated as shown below:

Small Entity

Large Entity

| For: | No. Filed | No. Extra |
|---|------------|-----------|
| Basic Fee | | |
| Total Claims | 4 - 20 = * | 0 |
| Indep Claims | 1 - 3 = * | 0 |
| <input type="checkbox"/> Multiple Dependent Claim (s) | | |

* If difference is less than zero
then enter '0' in second column

| Rate | Fee |
|-------|--------|
| | \$ 345 |
| x 9 | \$ |
| x 39 | \$ |
| + 130 | \$ |
| Total | \$ |

OR

| Rate | Fee |
|-------|--------|
| | \$ 690 |
| x 18 | \$ 0 |
| x 78 | \$ 0 |
| + 260 | \$ 0 |
| Total | \$ 690 |

☒

A check in the amount of \$ 690.00 is enclosed for the filing fee.

☒

The Commissioner is hereby authorized to charge any additional fees that may be required to
Deposit Account No. 50-1417.

Respectfully Submitted,

By:

Shrinath Malur

Registration No. 34,663

LIST OF INVENTORS' NAMES AND ADDRESSES

1. Tooru KAWASAKI, Hitachi, Japan.
2. Atsushi YUKITA, Hitachi, Japan.
3. Masato OHURA, Hitachi, Japan.
4. Yasuo YATOU, Hitachinaka, Japan.

Title of the Invention

RADIOACTIVE WASTE TREATMENT FACILITY

Inventors

Tooru KAWASAKI
Atsushi YUKITA
Masato OHURA
Yasuo YATOU

005220" 2364360

TITLE OF THE INVENTION

RADIOACTIVE WASTE TREATMENT FACILITY

BACKGROUND OF THE INVENTION

5 The present invention relates to a radioactive waste treatment facility for solidification of radioactive waste, which is generated from radioactive material handling facilities such as nuclear power plants, fuel reprocessing plants, and the like.

10 The radioactive waste generated from radioactive material handling facilities such as nuclear power plants, fuel reprocessing plants, and the like is generally solidified with a hydraulic solidifying material such as cement and the like. In accordance with the above
15 processing, not only the volume of the radioactive waste can be reduced, but also stable a solidified waste superior in long term duration can be obtained.

 Generally, the radioactive waste is classified to various groups having different properties each other such
20 as miscellaneous solid waste, concentrated liquid waste, spent resin, ashes, and others. Respective of the groups is handled with an appropriate treating method of injecting solidification or kneading solidification depending on its kind and properties.

25 The injecting solidification is a method, in which the waste is contained in a drum first, and then, a solidifying agent is injected into the drum from the top of the drum for solidification. The injecting

solidification method is applied to incombustible miscellaneous solid waste such as pipes and others, with which the solidifying agent can be flowed down through intervals among the solid waste.

5 The kneading solidification is a method, in which the waste is solidified by kneading with a solidifying agent. The kneading solidification method is applied to powder, granular, or liquid waste such as concentrated liquid waste and its dried powder, spent resin, ashes, and
10 the like. At this time, there are in-drum type and out-drum type for the kneading method. The in-drum type method is a method, in which, after charging the waste and a solidifying agent together into a solidifying container (or during charging), a kneading blade is inserted into
15 the charged materials to knead them. The out-drum type method is a method, in which, after charging the waste and a solidifying agent together into an exclusive kneading container and kneading the charged materials by inserting a kneading blade therein, the kneaded material is poured
20 into a solidifying container.

As explained above, the injecting solidification and the kneading solidification are different solidification methods each other. Therefore, in order to treat miscellaneous many kind radioactive wastes
25 adequately, an appropriate solidification facility must be provided respectively, and a significantly broad installation site area was required.

In order to solve the above problem, a radioactive

006280 296450
waste treatment facility (solidification facility)
comprising; a transferring means for transferring
solidifying containers; an out-drum mixer type kneader
which is capable of preparing kneaded material by charging
5 a solidifying agent, additive water, and the radioactive
waste together therein and kneading them; and a kneaded
material injecting means, which injects the kneaded
material into a solidifying container at a designated
location in the transferring direction of the transferring
10 means; is disclosed in JP-A-8-29594 (1996).

In accordance with the radioactive waste treatment
facility, when performing the injection and
solidification of the radioactive miscellaneous solid
waste and others, a solidifying container wherein the
15 radioactive waste is supplied previously is transferred
to a designated location by the transferring means; only
the solidifying agent and the additive water are charged
into the kneader to prepare a solidifying agent paste; and
the solidifying agent paste is injected into the
20 solidifying container by the kneaded material injecting
means. Accordingly, the solidifying agent paste is flowed
down through the intervals among the solid waste to be
filled into the solidifying container, and a solidified
waste as same as the one obtained by a normal injecting
25 solidification method can be prepared.

On the other hand, when concentrated liquid waste,
spent resin, ashes, and the like are solidified by the
kneading solidification, a solidified waste (homogeneous

006280" 2964962" 082900

solidified waste), wherein the solidifying paste and the radioactive waste are mixed thoroughly, as same as the one obtained by a normal injecting solidification method can be prepare by the steps of: transferring an empty
5 solidifying container to a designated location by the transferring means; charging a solidifying agent, additive water, and the radioactive waste into a kneading vessel of the kneader; agitating the charged material with kneading blade to form a kneaded material; and injecting
10 the kneaded material into the solidifying container by the kneaded material injecting means.

In accordance with the prior art described above, kneading the solidifying paste (solidifying agent + additive water) for kneading solidification, and kneading
15 the kneaded material for kneading solidification are performed by a similar out-drum-mixer type kneader, in order to make it possible to perform injecting solidification and kneading solidification together by a single facility.

20 However, in accordance with the above prior art, the following problems are still remained to be solved.

That is, the radioactive waste treating (solidification) facility must be cleaned up after completing a designated treatment. At that time, the
25 portions touched with the radioactive water are contaminated with radioactive material, and washed water of the portions become secondary radioactive waste and another treating facility for the secondary radioactive

waste becomes necessary. Accordingly, in the radioactive waste treating (solidification) facility, it is preferable that the portions touched with radioactive waste must be reduced as small as possible.

5 Generally, in case of out-drum type kneader is used in the kneading solidification, both the kneading blade and the kneading vessel are contaminated with radioactive material, and both of them must be washed. On the contrary, in case of in-drum type kneader is used, only the kneading
10 blade is contaminated. Therefore, only the kneading blade must be washed, and the amount of secondary radioactive material can be reduced.

 In accordance with the prior art, the out-drum mixer type kneader is used, in order to make it possible to
15 perform injecting solidification and kneading solidification together by a single facility. Accordingly, both the kneading blade and the kneading vessel are contaminated with radioactive material in the kneading solidification operation, and both of them must
20 be washed. Therefore, the amount of the secondary radioactive waste can be hardly reduced.

SUMMARY OF THE INVENTION

 One of the objects of the present invention is to
25 provide a radioactive waste treatment facility, which can perform both the injecting solidification and the kneading solidification together by a single facility, and makes it possible to reduce the generating amount of the

006220 2564350

secondary radioactive waste.

(1) In order to achieve the above object, the radioactive waste treatment facility of the present invention comprises;

5 a transferring means for transfer a solidifying container;

a solidifying agent kneading and injecting means for preparing a solidifying agent paste by kneading the solidifying agent and additive water, and injecting the
10 solidifying agent paste into the solidifying container at a first location in the upstream of the transferring direction of the transferring means; and

a waste charging and kneading means for charging the radioactive waste into the solidifying container at a
15 second location in the downstream, in comparison with the first location, of the transferring direction of the transferring means, and kneading the radioactive waste with the solidifying paste in the solidifying container.

In accordance with the radioactive waste treatment
20 facility of the present invention composed as described previously, when the injecting solidification of radioactive miscellaneous solid waste is performed, a solidifying container, wherein the radioactive waste is charged previously, is transferred to the first location
25 by the transferring means, and the solidifying paste is injected into the solidifying container by the solidifying agent kneading and injecting means. Therefore, as the solidifying paste is filled into the solidifying container

005280 2354950

by flowed down through the intervals among the radioactive waste, a solidified waste as same as the one obtained by the normal injecting solidification can be prepared.

On the other hand, when the kneading solidification
5 of radioactive concentrated liquid waste, spent resin, ashes, and others is performed, an empty solidifying container is transferred to the first location by the transferring means, and only the solidifying paste is injected into the solidifying container by the solidifying
10 agent kneading and injecting means. Subsequently, the solidifying container is transferred to the second location; the radioactive waste is charged into the solidifying container, wherein the solidifying paste is filled previously, by the waste charging and kneading means
15 at the second location; and kneading is performed in the solidifying container. Accordingly, a solidified waste (homogeneous solidified waste), the solidifying paste and the radioactive waste are mixed thoroughly, as same as the one obtained by the normal injecting solidification can
20 be prepared.

In accordance with the composition described above, the injecting solidification and the kneading solidification can be performed by a single facility, and the solidifying agent kneading and injecting means can be
25 made the out-drum type and the waste charging and kneading means can be made in-drum type.

At that time, the solidifying agent kneading and injecting means is used for kneading only the non-

radioactive solidifying agent and the non-radioactive additive water. Therefore, the solidifying agent kneading and injecting means can be installed in an area separated by, for instance, a separation wall from the area
5 where the waste charging and kneading means is installed. Because the liquid waste of washing is also non-radioactive, and it could be readily treated and deposited. On the other hand, the waste charging and kneading means is charged with radioactive waste when kneading and
10 solidifying. Therefore, the liquid waste from washing the waste charging and kneading means becomes the secondary radioactive waste. However, the waste charging and kneading means can be made in-drum type, and washing is necessary only for kneading blade. Accordingly, the
15 generating amount of the secondary radioactive waste can be reduced.

(2) In accordance with the above methods described in (1), the solidifying agent kneading and injecting means desirably comprises;

20 a kneading vessel, whereto the solidifying agent and the additive water is charged;

a first kneading blade for agitating inside of the kneading vessel;

an out-drum type kneader for preparing the
25 solidifying agent paste; and

an injecting means for injecting the solidifying agent paste in the kneader for preparing the solidifying agent paste into the solidifying container.

005230 2366455

(3) In accordance with the above methods described in (1), the waste charging and kneading means desirably comprises;

an elevating means for elevating the solidifying container, which has been transferred to the second location by the transferring means, upward from the transferring line of the transferring means; and

an in-drum type radioactive waste kneader, which charges the radioactive waste into the elevated solidifying container and performs kneading in the solidifying container with the second kneading blade.

(4) In accordance with the above methods described in (1), the solidifying agent injecting and kneading means is desirably provided in an area separated from the waste charging and kneading means by separating walls.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, features and advantages of the present invention will be understood more clearly from the following detailed description with reference to the accompanying drawings, wherein,

FIG. 1 is a flow diagram for explaining the behavior at the kneading and solidifying operation of the solidifying agent kneading and injecting means and the waste charging and kneading means, which are provided in the radioactive waste solidification facility of the embodiment of the present invention,

FIG. 2 is a set of schematic illustrations indicating the transferring route of the solidifying container in the transferring mechanism, which is provided in the radioactive waste solidification facility of the embodiment of the present invention,

FIG. 3 is a schematic illustration indicating a total outline of the compositions of the solidifying agent injecting and kneading mechanism and the waste charging and kneading mechanism, which are provided in the radioactive waste solidification facility of the embodiment of the present invention,

FIG. 4 is a schematic illustration indicating the composition of the turn-table indicated in FIG. 2(a) and FIG. 2 (b), and

FIG. 5 is a flow diagram for indicating the behavior at the injecting and solidifying operation of the solidifying agent kneading and injecting means indicated in FIG. 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, details of the embodiments of the present invention is explained referring to the figures 1 to 5.

The solidification facility of the present embodiment is capable of solidifying four kinds of radioactive waste, i.e. the miscellaneous solid waste, spent resin, dried powder of concentrated liquid waste, and ashes, into a solidifying container (details will be

explained later), into a solidifying container 4.

The solidification facility comprises;

a solidifying agent injecting and kneading
mechanism 50 (details will be explained later) for
5 injecting and solidifying the miscellaneous solid waste
(hereinafter, called only as injecting solidification),
and for injecting the solidifying agent paste at kneading
and solidifying the spent resin, the dried powder of
concentrated liquid waste, and the ashes (hereinafter,
10 called only as kneading solidification);

a waste charging and kneading mechanism 60 (details
will be explained later) for charging the radioactive waste
and kneading at the kneading solidification;

and a transferring mechanism 5 (detail will be
15 explained later) for transferring the solidifying
container 4 (details will be explained later) selectively
to the solidifying agent injecting and kneading mechanism
or the waste charging and kneading mechanism depending on
whether the operation is for the injecting solidification
20 or the kneading solidification.

FIG. 2(a) and FIG. 2(b) are figures indicating the
transferring route of the solidifying container 4 of the
transferring mechanism 5 described above.

In accordance with FIG. 2(a) and FIG. 2(b), the
25 transferring mechanism 5 is composed of, for instance, a
plurality of rollers 50 arranged in a transferring
direction (so-called roller conveyer, refer to FIG. 4);
respective of the rollers is central-controlled by control

signals (not shown in the figure) from the controller 70 installed in a control room (not shown in the figure) of the solidification facility.

The transferring mechanism 5 comprises; a main
5 transferring route 5A; a sub-start up point route 5B, which merges with the main transferring route at a point of downstream side in the transferring direction near the start up point of the main transferring route 5A; and a sub-transferring route 5C, which branches at a point of
10 downstream side from the merging point of the sub-start up point route 5B with the main transferring route 5A, and merges again with the main transferring route at a point of further downstream side from the branching point. Respective of the turn-tables 5a₁-5a₃, is provided at the
15 respective of the merging point of the main transferring route 5A with the sub-start up point route 5B, and the merging point and the branching point of the main transferring route 5A with the sub-transferring route 5C. The turn-tables are controlled automatically by the
20 controller 70 (or manual control by inputting operation signals from the control panel to the controller 70 can be used) to switch the transferring route of the solidifying container 4 (detail will be explained later).

A sensor 80 (refer to FIG. 2) for detecting the
25 solidifying container 4 when it is transferred is provided at the first position 5b on the main transferring route 5A (or a position before the first position 5b by a designated distance can be used). When detecting signals

(refer to FIG. 2 (a)) from the sensor 80 is transmitted to the controller 70, corresponding control signals (not shown in the figure) are output to the main transferring route 5A from the controller 70, and the solidifying container is stopped once at the first position 5b. The solidifying agent injecting and kneading mechanism 50 is provided at upper position of the first position 5b. A total outline of the compositions of the solidifying agent injecting and kneading mechanism 50 is indicated in FIG. 3(a).

In accordance with FIG. 3(a), the solidifying agent injecting and kneading mechanism 50 comprises;

a solidifying agent silo 11;

a solidifying agent weighing apparatus 1 for weighing the solidifying agent, which is supplied from the solidifying agent silo 11 via the solidifying agent supply valve 16;

an additive water supply line 12;

an additive water weighing apparatus 2 for weighing the additive water, which is supplied from the additive water supply line 12 via the additive water supply valve 23;

a kneader 3 for solidifying agent, which kneads the solidifying agent supplied from the solidifying agent weighing apparatus 1 through the solidifying agent supply valve 17 and the additive water supplied from the additive water weighing apparatus 2 via the additive water supply valve 18 to prepare the solidifying agent paste, and

an injection valve 19 for injecting and filling the solidifying agent paste into the solidifying container 4.

The kneader 3 for solidifying agent is out-drum type apparatus comprising a kneading vessel 3a, whereto the solidifying agent and the additive water are supplied, and a kneading blade (agitating blade) 3b driven by a motor for agitating inside of the kneading vessel 3a.

Open-close operations of the waste supply valves 24a-24c and the waste supply valves 20a-20c are controlled by control signals from the controller 70 such as electric magnet valves, but details are omitted from the figures.

The whole solidifying agent injecting and kneading mechanism 50 composed as described above is installed in an area separated from the area where the other radioactive handling apparatus and facilities such as the waste charging and kneading mechanism 60 and others by, for instance, separating walls.

A sensor 81 (refer to FIG. 2) for detecting the solidifying container 4 when it is transferred there is provided at a second location 5c (at a position before a designated distance) in the sub-transferring route 5B (that is, at downstream side in the transferring direction from the first location) as indicated in FIG. 2 (a) and FIG. 2 (b). When the detecting signals of the sensor 81 'refer to FIG. 2) is transmitted to the controller 70, corresponding control signals are output from the controller 70 to the transferring mechanism sub-transferring route 5B, and the solidifying container 4 is

stopped once at the second location 5c. The waste charging and kneading mechanism 60 is installed at the location upward the second location 5c. A whole schematic composition of the waste charging and kneading mechanism 5 60 is indicated in FIG. 3 (b).

In accordance with FIG. 3 (b), the waste charging and kneading mechanism 60 comprise;

waste supply lines 13a-13c for supplying radioactive waste,

10 waste weighing apparatus 6a-6c for weighing the radioactive waste supplied from the waste supply lines 13a-13c via the waste supply valves 24a-24c,

a waste supply line 21 for supplying the radioactive waste, which is weighed at respective of the waste weighing 15 apparatus 6a-6c, via the waste supply valves 20a-20c,

a solidifying container elevator 10 for elevating the solidifying container 4, which is transferred to the second location 5c, upwards from the transferring line 5C (refer to FIG. 1, explained later), and

20 a kneader 9 for kneading waste, which charges the radioactive waste supplied from the waste supply line 21 into the elevated solidifying container 4, and kneads the radioactive waste in the solidifying container 4.

The kneader 9 for kneading waste is so-called in-drum 25 type, which is provided with only kneading blade 9a (agitating blade) driven by motor for agitating inside of the solidifying container 4, and is composed so as to charge the radioactive waste supplied from the waste supply line

21 into the elevated solidifying container 4, and to knead the radioactive waste in the solidifying container 4 by dipping the kneading blade 9a therein (refer to FIG. 1, explained later).

5 The solidifying container elevator 10 comprises a base 10a; an extendable arm mechanism 10b provided with, for instance, a hydraulic cylinder; and a solidifying container platform 10c located at the second location 5c in the sub-transferring route 5C; and the solidifying
10 container platform 10c can be elevated or lowered depending on extending-shrinking motion of the extendable arm mechanism 10b corresponding to extending-shrinking motion of the hydraulic cylinder.

 The number of the waste supply lines 13a-13c, waste
15 supply valves 24a-24c, waste weighing apparatus 6a-6c, and the waste supply valves 20a-20c to be provided are decided depending on the number of kinds of waste to be kneaded and solidified. For instance, spent resin is supplied through the waste supply line 13a, dried powder of
20 concentrated liquid waste is supplied through the waste supply line 13b, and ashes is supplied through the waste supply line 13c.

 The solidifying agent supply valve 16, the solidifying agent supply valve 17, the additive water
25 supply valve 23, and the additive water supply valve 18 are controlled their open-close motion 8for instance electric magnet valve) by the control signals from the controller 70, but details are omitted in the figure.

The whole waste charging and kneading mechanism 60 composed of the apparatus as explained above is installed in a radioactivity controlled area separated from the area where the other non-radioactive handling apparatus and facilities such as the solidifying agent injecting and kneading mechanism 50 and others by the separating walls 27 (refer to FIG. 3 (a)).

FIG. 4 is a schematic illustration indicating the composition of the turn-table 5a1 indicated in FIG. 2(a) and FIG. 2 (b). The turn-table 5a is not operated for a special motion when the solidifying container 4 moves in a straight direction on the main transferring route 5A (that is, when it moves as route 5A1 \rightarrow turn-table 5a1 \rightarrow route 5A). However, when the moving direction must be changed (that is, when it moves as route 5A1 \rightarrow turn-table 5a1 \rightarrow route 5C), the turn-table is operated as follows.

That is, a sensor 82 for detecting the solidifying container 4 when it is transferred is provided at a designated position on the turn-table 5a1 (or a position at a designated distance before the designated position on the route 5A1 can be used). When a detecting signal of the sensor 82 is transmitted to the controller 70, a stop controlling signal (not shown in the figure) corresponding to the detecting signal is output from the controller 70 to the driving roller 50 on the turn-table 5a1, and the solidifying container 4 is stopped once on the turn-table 5a1.

Then, a control signal is output from the controller

70 to the driving device 83 for rotating the turn-table 5a1, and the turn-table 5a1 is rotated by 90 degrees in a direction indicated by an arrow A in FIG. 4.

After completing the rotation, a driving control
5 signal (not shown in the figure) is output from the controller 70 to the driving roller 50 on the turn-table 5a1, and the transfer is resumed by transferring the solidifying container 4 to the sub-transferring route 5C from the turn-table 5a1.

10 Other two turn-tables 5a2, 5a3 are composed as same as above, but explanation is omitted.

As explained above, the transferring mechanism 5
composes the transferring means for transferring the solidifying container as claimed in respective of the
15 claims.

A first kneading blade comprises the kneading blade 3b of the kneader 3 for solidifying agent, and the injecting means for injecting the solidifying agent paste in the kneader for solidifying agent comprises the injecting
20 valve 19.

The solidifying agent injecting and kneading means for injecting the solidifying agent paste into the solidifying container at the first location in the upstream side in the transferring direction of the transferring means comprises; solidifying agent silo 11, solidifying
25 agent supply valve 16, solidifying agent weighing apparatus 1, solidifying agent supply valve 17, additive water supply valve 23, additive water weighing apparatus

2, additive water supply valve 18, kneader 3 for solidifying agent, and injecting valve 19.

An elevating means for elevating the solidifying container, which is transferred to the second location by the transferring means, upwards from the transferring line of the transferring means comprises the solidifying container elevator 10, and the second kneading blade comprises the kneading blade 9a of the kneader 9 for waste.

The waste charging and kneading means, which is capable of charging radioactive waste into the solidifying container at the second location in the downstream of the first location in the transferring direction of the transferring means and of kneading the radioactive waste in the solidifying container, comprises waste supply lines 13a-13c, waste supply valves 24a-24c, waste weighing apparatus 6a-6c, waste supply valves 20a-20c, waste supply lines 21, and kneader 9 for waste.

The separating wall is composed of partition walls 27.

Operation of the radioactive solidification facility composed as explained above of the present embodiment is explained hereinafter.

In accordance with the solidification facility, an instruction for switching an injecting and solidifying mode for performing the injection and solidification, and a kneading and solidifying mode for performing kneading and solidification is input at the control room, and corresponding signal is output to the controller 70. Then,

the controller 70 controls automatically respective of the apparatus so as to operate appropriately corresponding to respective of the wastes.

(1) Injection and solidification

5 When the injecting and solidifying mode is selected in the control room, the solidifying container 4 is transferred by the route indicated in FIG. 2 (a), and the solidification treatment is performed. The process is explained referring to FIG. 2 (a) and FIG. 5.

10 In accordance with FIG. 2(a), the solidifying container 4, wherein miscellaneous solid waste has been charged by operators previously, is loaded on the main transferring route 5A, and transferred to the first location 5b by the transferring mechanism 5 and stopped
15 once.

In a condition that the solidifying container 4 is stopped at the first location 5b, an adequate amount of solidifying agent for injection and solidification of the miscellaneous solid waste is weighed by the solidifying
20 agent weighing apparatus 1, and injected into the kneader 3 for solidifying agent. Subsequently, an adequate amount of additive water for injection and solidification of the miscellaneous solid waste is weighed by the additive water weighing apparatus 2, and injected into the kneader 3 for
25 solidifying agent. The solidifying agent and the additive water injected into the kneader 3 for solidifying agent is kneaded under a designated condition to be the solidifying agent paste, and injected into the solidifying

005280-29564950

container 4. The solidifying agent paste flows down through the intervals among the waste to fill the inside of the solidifying container 4. Accordingly, a solidified waste as same as the one obtained by the normal injection and solidification can be prepared.

The solidified waste of the miscellaneous solid waste obtained as above is transferred as it is on the main transferring route 5A by the transferring mechanism 5, and stored in a storage place (not shown in the figure).

10 (2) Kneading and solidification

When the kneading and solidifying mode is selected in the control room, the solidifying container 4 is transferred by the route indicated in FIG. 2 (b), and the solidification treatment is performed. The process is explained referring to FIG. 2 (b) and FIG. 1.

In accordance with FIG. 2(b), the solidifying container 4 starts the sub-original point 5B as it is empty, which is different from the previous (1). The solidifying container 4 loaded on the sub-original point 5B is changed its transferring direction by the turn-table 5a1 to the main transferring route 5A, and transferred to the first location 5b by the transferring mechanism 5 and stopped once.

In a condition that the solidifying container 4 is stopped at the first location 5b, an adequate amount of solidifying agent for treating the waste (hereinafter, called selected waste) selected at the control room from spent resin, dried powder of concentrated liquid waste,

and ashes is weighed by the solidifying agent weighing apparatus 1, and injected into the kneader 3 for solidifying agent, as indicated in FIG. 1. Subsequently, an adequate amount of additive water for solidification of the selected waste is weighed by the additive water weighing apparatus 2, and injected into the kneader 3 for solidifying agent. The solidifying agent and the additive water injected into the kneader 3 for solidifying agent is kneaded under a designated condition to be the solidifying agent paste having an adequate water-cement ratio and weight for kneading and solidification of the selected waste, and injected into the solidifying container 4.

The solidifying container 4 injected by the solidifying agent paste is transferred on the main transferring route 5A by the transferring mechanism 5, and changed its transferring direction by the turn-table 5a2 to the sub-transferring route 5C. The solidifying container 4 is transferred further to the second location 5c on the sub-transferring route 5C, and stopped there once.

Under the condition that the solidifying container 4 is stopped at the second location 5c, the solidifying container 4 is elevated by the solidifying container elevator 10, which is installed under the kneader 9 for waste, until the upper periphery 4a (an opening portion) of the solidifying container 4 is touched with the lid portion 9b of the kneader 9 for waste. In this condition,

under agitation and kneading by driving the kneading blade 9a, a designated amount of selected waste is charged into the solidifying container 4 from the waste weighing apparatus 6a-6c corresponding to the selected waste.

5 Accordingly, a solidified waste, wherein the solidifying agent paste and the selected waste are mixed thoroughly, as same as the solidified waste (homogeneous solidified waste) obtained by the normal kneading and solidification can be prepared.

10 At this time, the kneading is continued for a designated time after completion of charging the total amount of the selected waste. After completion of the kneading, the solidifying container 4 is lowered to the level of the transferring mechanism 5 again by the
15 solidifying container elevator 10. During the above operation, the upper periphery 4a of the solidifying container 4 and the lower plane of the lid portion 9b of the kneader for waste is contacted tightly in order to prevent the kneaded material in the solidifying container
20 4 from splashing out.

 The homogeneous solidified waste obtained as described above is transferred on the sub-transferring route 5C again, changed its transferring direction by the turn-table 5a3 on the main transferring route 5A, and
25 transferred on the main transferring route 5A to a storage place which is not shown in the figure.

 In accordance with the solidifying facility of the present embodiment, which is composed as described above,

the injection and solidification of miscellaneous solid waste and kneading and solidification of a several kinds of waste can be performed selectively by a single facility.

Furthermore, the solidifying agent injecting and
5 kneading mechanism 50 can be made out-drum type, and the waste charging and kneading mechanism 60 can be made in-drum type.

In any cases of the above injection- solidification and kneading-solidification, the solidifying agent
10 injecting and kneading mechanism 50 is used only for kneading the non-radioactive solidifying agent and the additive water. Therefore, the solidifying agent injecting and kneading mechanism 50 can be installed in an area separated by a partition wall 27 from the area where
15 the waste charging and kneading mechanism 60, which is radioactive apparatus, is installed, and generated washing liquid waste can be treated and disposed readily because the liquid waste is non-radioactive. On the other hand, the waste charging and kneading mechanism 60 is
20 radioactive because the radioactive waste is charged when kneading and solidifying, and the generated washing liquid waste becomes radioactive secondary waste. However, the waste charging and kneading mechanism 60, which is a
25 washing object is only the kneading blade 9a. Therefore, the generating amount of the radioactive secondary waste can be made small.

Generally, the solidifying agent paste prepared by

kneading the solidifying agent and the additive water has a low viscosity, but the adding the waste and kneading increases the viscosity. In accordance with the out-drum type (kneading vessel + kneading blade) kneading and solidification, the increased viscosity of the kneading material generates a possibility to choke the outlet of the kneading vessel when the kneaded material is discharged.

In accordance with the present embodiment, an advantage is realized that the choke described above can be prevented, because kneading the solidifying agent paste having a low viscosity is performed by the out-drum type solidifying agent injecting and kneading mechanism 50, and kneading the radioactive waste is performed by the in-drum type waste charging and kneading mechanism 60.

In accordance with the present embodiment, changing the transferring direction of the solidifying container 4 is performed using the turn-table 5a by turning the turn-table 5a by 90 degrees under a condition that the solidifying container is loaded on the turn-table 5a, but methods of changing the transferring direction is not restricted to the above method, and other method is usable.

That is, when the solidifying container 4 is stopped on the turn-table 5a, for instance, the solidifying container 4 is transferred to the sub-transferring route 5C by hanging the solidifying container 4 with a hanger which is provided particularly, by pushing the solidifying container 4 to the direction toward the sub-transferring

route 5C with a pusher which is provided particularly, or
other transferring mechanism, which has a function to
transfer the solidifying container 4 to the sub-
transferring route 5C, inserted beneath driving rollers
5 50 of the turn-table 5a to operate between the rollers 50.

In accordance with the present invention, the
injection and solidification operation and kneading and
solidification operation can be performed selectively by
a single facility, and generating amount of the radioactive
10 secondary waste can be decreased.

335233 " 2364363

What is claimed is;

1. A radioactive waste treatment facility comprising;
a transferring means for transferring solidifying
5 container,

a solidifying agent injecting and kneading means for
preparing a solidifying agent paste by kneading a
solidifying agent and additive water, and injecting said
solidifying agent paste into said solidifying container
10 at a first location of the upstream side in a transferring
direction of said transferring means, and

a waste charging and kneading means, which is capable
of charging radioactive waste into said solidifying
container at the second location in the downstream of the
15 first location in the transferring direction of the
transferring means and of kneading the radioactive waste
in said solidifying container.

2. A radioactive waste treatment facility as claimed
20 in claim 1, wherein;

said solidifying agent injecting and kneading
means comprises;

a kneading vessel, whereto the solidifying agent and
the additive water is supplied;

25 a first kneading blade for agitating inside of said
kneading vessel;

an out-drum type kneader of solidifying agent for
preparing said solidifying agent paste; and

an injecting means for injecting said solidifying agent paste in said kneader of solidifying agent into said solidifying container.

- 5 3. A radioactive waste treatment facility as claimed in claim 1, wherein;

said waste charging and kneading means comprises;

- an elevating means for elevating said solidifying container, which has been transferred to the second
10 location by said transferring means, upward from transferring line of said transferring means; and

- an in-drum type waste kneader, which charges radioactive waste into said elevated solidifying container and performs kneading in said solidifying
15 container with second kneading blades.

4. A radioactive waste treatment facility as claimed in claim 1, wherein;

- said solidifying agent injecting and kneading
20 means is installed in an area separated by partition wall from said waste charging and kneading means.

The injection and solidification operation and kneading and solidification operation can be performed selectively by a single facility, and generating amount of the radioactive secondary waste can be decreased.

A transferring means 5 for transferring solidifying container 4; a solidifying agent injecting and kneading means 50 for preparing a solidifying agent paste by kneading a solidifying agent and additive water, and injecting said solidifying agent paste into said solidifying container 4 at a first location 5b of the upstream side in a transferring direction of the transferring means 5; and a waste charging and kneading means 60, which is capable of charging radioactive waste into the solidifying container 4 at the second location 5c in the downstream of the first location 5b in the transferring direction of the transferring means 5 and of kneading the radioactive waste in the solidifying container 4; are provided.

FIG. 1

(NON-RADIOACTIVE APPARATUS)

(RADIOACTIVE APPARATUS)




FIG. 2(a)




FIG. 2(b)




FIG. 3(a)

(NON-RADIOACTIVE APPARATUS)





FIG. 3(b)

(RADIOACTIVE APPARATUS)





FIG. 4





FIG. 5

(NON-RADIOACTIVE APPARATUS)



Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

RADIOACTIVE WASTE TREATMENT FACILITY

上記発明の明細書（下記の欄で×印がついていない場合は、本書に添付）は、

The specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on _____
(if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示している。

Prior Foreign Application(s)

外国での先行出願

| | |
|-----------|-----------|
| 11-356466 | Japan |
| (Number) | (Country) |
| (番号) | (国名) |
| | |
| (Number) | (Country) |
| (番号) | (国名) |

私は、第35編米国法典119条(e)項に基づいて下記の米国外特許出願規定に記載された権利をここに主張いたします。

| | |
|-------------------|---------------|
| (Application No.) | (Filing Date) |
| (出願番号) | (出願日) |

私は、下記の米国法典第35編120条に基づいて下記の米国外特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

| | |
|-------------------|---------------|
| (Application No.) | (Filing Date) |
| (出願番号) | (出願日) |
| | |
| (Application No.) | (Filing Date) |
| (出願番号) | (出願日) |

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

| | |
|------------------------|--------------------------|
| 15/December/1999 | <input type="checkbox"/> |
| (Day/Month/Year Filed) | |
| (出願年月日) | |
| | |
| (Day/Month/Year Filed) | <input type="checkbox"/> |
| (出願年月日) | |

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

| | |
|-------------------|---------------|
| (Application No.) | (Filing Date) |
| (出願番号) | (出願日) |

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

| | |
|--|--|
| (Status: Patented, Pending, Abandoned) | |
| (現況: 特許許可済、係属中、放棄済) | |
| | |
| (Status: Patented, Pending, Abandoned) | |
| (現況: 特許許可済、係属中、放棄済) | |

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration
(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の
手続きを米特許商標局に対して遂行する弁理士または代理人
として、下記の者を指名いたします。(弁理士、または代理
人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint
the following attorney(s) and/or agent(s) to prosecute this application
and transact all business in the Patent and Trademark Office
connected therewith (list name and registration number)

Thomas E. Beall, Jr., Reg. No.22,410; John R. Mattingly, Reg.
No.30,293; Daniel J. Stanger, Reg. No.32,846; Shrinath Malur, Reg.
No.34,663; Gene W. Stockman, Reg. No.21,021; Jeffrey M.
Ketchum, Reg. No.31,174; and Scott W. Brickner, Reg. No.34,553.

書類送付先

Send Correspondence to:

MATTINGLY, STANGER & MALUR, P.C.
104 East Hume Avenue
Alexandria, Virginia 22301

直接電話連絡先：(氏名及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Telephone: (703) 684-1120

Fax: (703) 684-1157

| | |
|------------|---|
| 唯一または第一発明者 | Full name of sole or first inventor Tooru KAWASAKI |
| 発明者の署名 | Inventor's signature Tooru Kawasaki |
| 日付 | Date 8/21/2000 |
| 住所 | Residence Hitachi, Japan |
| 国籍 | Citizenship Japan |
| 私書箱 | Post Office Address c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan |

(第二以降の共同発明者についても同様に記載し、署名をす
ること)

(Supply similar information and signature for second and
subsequent joint inventors.)

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

| | | |
|------------|---|---|
| 第二共同発明者 | Full name of second joint inventor, if any Atsushi YUKITA | |
| 第二共同発明者の署名 | 日付 | Second inventor's signature Date <i>Atsushi Yukita</i> 8/21/2000 |
| 住所 | Residence Hitachi, Japan | |
| 国籍 | Citizenship Japan | |
| 私書箱 | Post Office Address c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan | |
| 第三共同発明者 | Full name of third joint inventor, if any Masato OHURA | |
| 第三共同発明者の署名 | 日付 | Third inventor's signature Date <i>Masato Ohura</i> 8/21/2000 |
| 住所 | Residence Hitachi, Japan | |
| 国籍 | Citizenship Japan | |
| 私書箱 | Post Office Address c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan | |
| 第四共同発明者 | Full name of fourth joint inventor, if any Yasuo YATOU | |
| 第四共同発明者の署名 | 日付 | Fourth inventor's signature Date <i>Yasuo Yaton</i> 8/21/2000 |
| 住所 | Residence Hitachinaka, Japan | |
| 国籍 | Citizenship Japan | |
| 私書箱 | Post Office Address c/o Hitachi Engineering Co., Ltd. 2-1, Saiwai-cho 3-chome, Hitachi-shi, Ibaraki 317-0073, Japan | |
| 第五共同発明者 | Full name of fifth joint inventor, if any | |
| 第五共同発明者の署名 | 日付 | Fifth inventor's signature Date |
| 住所 | Residence | |
| 国籍 | Citizenship | |
| 私書箱 | Post Office Address | |

(第六以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for sixth and subsequent joint inventors.)